

LED SHADOWLESS OPERATING LAMP

YDE 700/500

LED shadowless
operating lamp



The main technical data

Technical data	unit	700 lamp head	500 lamp head
Spot center illumination in color temperature 5000K	Lux	160,000--200,000	140,000--180,000
Color temperature	K	4000-5000	4000-5000
Ra		95	95
50% Spot diameter d50	mm	150	150
10% Spot diameter d50	mm	300	300
Illuminance depth	cm	80	100
Illuminance adjusting range	%	25-100	25-100
Ultraviolet irradiance wavelength under 40nm	W/m ²	≤0.002	≤0.002
Focal distance adjusting mode		Manual/ electric(optional)	Manual/ electric(optional)
Beads power	W	1W/unit×60beads	1W/unit×45beads
Power supply		110V/220V 50Hz/60Hz	110V/220V 50Hz/60Hz
Input power	W	100	80
LED average life	H	≥100□000	≥100□000
LAMP HEAD DIAMETER	MM	700	500
INSTALLATION CEILING HEIGHT	M	2.8(ADJUSTABLE)	2.8(ADJUSTABLE)

Exclusive Distributor



PT. PERMANA PUTRA MANDIRI
 MEDICAL EQUIPMENTS SUPPLIES AND SERVICES
 Jl. Taman Mini Indonesia Indah (TMII)
 Pintu II Atas No. 43 Cipayung, Jakarta Timur, Indonesia
 Telp. : +62-21 841 5976, Fax : +62-21 840 7865
 Email : info@ptppm.id, Website : www.ptppm.id