

YDZ-SERIES INTEGRAL REFLECTION SHADOWLESS OPERATING LAMPS

B-series: Luxurious square-arm shadowless lamp YDZ700/500



Main technical parameters

Specification	YDZ700/500
Maximum illuminance	120, 000/80, 000
Color temperature	4200K±500K
Spot diameter	200±100 mm
Lighting depth	≥80cm
Brightness adjustment	Eight gears dimmer system
Temperature rise on the surgeon's head	≤2°/ ≤2°
Color rendering index	≥95%
Supply voltage	220V±22V 50Hz±1Hz
Input power	500W
Bulb power	150/150
Automatic switch of king/auxiliary bulb	√
Lowest installation height of single bending lamp	2800mm

The focusing system of the lamp is exquisite in structure, making it easier and more convenient to replace the bulb and holder. Jacket of the handle can be removed for high-temperature ($\leq 134^{\circ}\text{C}$) sterilization.

The lamp is also equipped with a function to automatically switch the backup bulbs. When the king bulb burns out, the auxiliary bulb will light up automatically within 0.2 seconds. There are arranged with indicators for failure of king/auxiliary bulb on the handle panel, reminding for timely replacement after operation.

Exclusive Distributor



PT. PERMANA PUTRA MANDIRI
 MEDICAL EQUIPMENTS SUPPLIES AND SERVICES
 Jl. Taman Mini Indonesia Indah (TMII)
 Pintu II Atas No. 43 Cipayung, Jakarta Timur, Indonesia
 Telp. : +62-21 841 5976, Fax: +62-21 840 7865
 Email : info@ptppm.id, Website: www.ptppm.id